



**Multi-Biometric
Time Attendance & Access Control System
uFace-302**



Storage Capacity

Face Capacity : 3,000
Fingerprints Capacity : 4,000
ID Card Capacity : 10,000
Transaction Capacity : 1,00,000
Push Data : Yes
Communication : TCP/IP, RS232/485, USB Host
Display : 4.3-Inch Touch Screen

Standard Functions

Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID Access Control Interfaces for: 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm Wiegand : Output

Optional Functions

MiFare Card, Wi-Fi, 3G, 2000 mAh Backup Battery, FR-1200

Power & Environment

Power Supply : 12V 3A
Operating Temperature : 0 °C ~ 45 °C
Operating Humidity : 20% - 80%
Dimension (in mm) : 193.6 x 165.2 x 86
Package Weight : 1.6 kg

Features

- Multi-languages
- High verification speed
- Advanced and user-friendly UI
- Chip encryption for firmware protection
- Optional built-in battery backup providing approximately 4 hours of continuous operation
- Easy to extend functions and customize client's requirements
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo, enhancing the security level of verification

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development